


Safely guide suspended loads or reach for tag lines and rigging.

Each SHT3 is enhanced with a Carbon Fiber sleeve on the neck where the tooling head is mounted. This increases the tool's strength significantly. The tapped end of our type 3 tool's internally threaded plug enables the use of our lap link and other specialty tools with the original push/pull head.

- Push/Pull Hooks on Y-head
- Graphite Reinforced Head Joint
- Extreme Temperature Durable Head
- Reflective Tape
- Safety Yellow Fiberglass Reinforced Pipe
- Large Protective Hand Grip
- Reflective Label



Tapped End Plug



Lap Link Tool



Large Protective Grip

| MODEL | DESCRIPTION | OVERALL LENGTH | WEIGHT |
|---------|----------------------------------|----------------|---------|
| SHT3-42 | 42" TAPPED HANDLE PUSH/PULL TOOL | 37-1/4" | 2.5LBS |
| SHT3-50 | 50" TAPPED HANDLE PUSH/PULL TOOL | 45-1/2" | 2.75LBS |
| SHT3-72 | 72" TAPPED HANDLE PUSH/PULL TOOL | 81" | 4LBS |

SITE SPECIFIC SOLUTIONS AVAILABLE ON REQUEST.
RATINGS: LOAD TESTING - STATIC PULL = 400 LBS. / COMPRESSION = 600 LBS. OUR TOOLS ARE NOT LIFTING/LOAD BEARING TOOLS, SWL CERT NOT REQUIRED. MAJOR COMPONENTS TESTED TO ASTM STANDARDS. SEEKING NOPSA (AU) REVIEW.
MADE IN USA.