



Safely guide suspended loads or reach for tag lines and rigging.

Each SHT3 is enhanced with a Carbon Fiber sleeve on the neck where the tooling head is mounted. This increases the tool's strength significantly. The tapped end of our type 3 tool's internally threaded plug enables the use of our lap link and other specialty tools with the original push/pull head.

- Push/Pull Hooks on Y-head
- Graphite Reinforced Head Joint
- Extreme Temperature Durable Head
- Reflective Tape
- Safety Yellow Fiberglass Reinforced Pipe
- Large Protective Hand Grip
- Reflective Label



Tapped End Plug



Lap Link Tool



Large Protective Grip

MODEL	DESCRIPTION	OVERALL LENGTH	WEIGHT
SHT3-42	42" TAPPED HANDLE PUSH/PULL TOOL	37-1/4"	2.5LBS
SHT3-50	50" TAPPED HANDLE PUSH/PULL TOOL	45-1/2"	2.75LBS
SHT3-72	72" TAPPED HANDLE PUSH/PULL TOOL	81"	4LBS

SITE SPECIFIC SOLUTIONS AVAILABLE ON REQUEST.

RATINGS: LOAD TESTING - STATIC PULL = 400 LBS. / COMPRESSION = 600 LBS. OUR TOOLS ARE NOT LIFTING/LOAD BEARING TOOLS, SWL CERT NOT REQUIRED. MAJOR COMPONENTS TESTED TO ASTM STANDARDS. SEEKING NOPSA (AU) REVIEW.

MADE IN USA.

www.billyphugh.com

bpc@billyphugh.com

+1 (361) 884-9351