

Get a firm grip on suspended pipe loads with the Stiffy Snare Tool.

Its innovative design lets you safely snare and guide pipes to their destination, keeping your hands out of harm's way. No more struggling with cumbersome ropes or risking injury from manual handling.

Upgrade your pipe handling practices with the Stiffy Snare Tool. **Order yours today!**

- Non-kinking Polyurethane Cable
- Over 600 lb Pull Capacity
- Designed for Industrial Use
- Built with Non-corrosive Materials



Drop Prevention Ring



Slide Grip Assembly



Tool Head



Releasable Loop



Lock Lever

MODEL	LENGTH	CAPACITY	WEIGHT
NST-24	24"	9"-13"	2.75LBS
NST-36	36"	2.5"-13"	3LBS
NST-48	48"	2.5"-13.75"	3.25LBS
NST-60	60"	2.5"-14.5"	3.75LBS

CUSTOM CABLE LENGTHS AVAILABLE UPON REQUEST

www.bilypugh.com

bpc@bilypugh.com

+1 (361) 884-9351 | blaser@bilypugh.com

OPERATING INSTRUCTIONS

**POLYURETHANE
CABLE**



Using Tool with Closed Loop

1. Slide polyurethane cable over end of load
2. Grip slide handle
3. Depress slide lock button
4. Slide grip towards butt cap to tighten polyurethane tube to load
5. Guide load to desired location
6. Depress slide lock button and slide grip forward towards load, to release polyurethane cable
7. Slide polyurethane cable off end of load

Releasing Polyurethane Cable

1. Grab slide handle, press slide lock button, slide handle forward to release tension on cable
2. Pivot release knob locking lever, depress and turn release knob clockwise
3. Press release and pull back on tool, cable will release from head

**CABLE INSERT
LOCATION**



**RELEASE
KNOB**



**LOCKING
LEVER**



Re-inserting Polyurethane Cable

1. Grab slide handle, press slide lock button and slide handle to top of shaft
2. Insert polyurethane cable into tool head (marked on side of tool head). Push in until it clicks. Depress and turn counter clockwise to locked position, pivot release knob locking lever down towards release knob
3. Tool is now ready to work